

## Specification

<b>Division</b>	<b>KRSRF</b>	<b>KSRST</b>	<b>KSRCT</b>
<b>Standard</b>	ASME Code Sec.VIII, KS B ISO 4126, API RP520, KOSHA Code, FDC Standard		
<b>Size</b>	1/2" ~ 18"	1/2" ~ 48"	1/2" ~ 40"
<b>Set. Pressure</b>	5 ~ 700kg/cm <sup>2</sup>	15 ~ 1500kg/cm <sup>2</sup>	
<b>Temperature</b>	Max. 593°C	Max. 593°C	
<b>Material</b>	C.S, SUS, Duplex, Nickel, Inconel, Monel, Hastelloy, Titanium, Tantalium, Special Alloy, Aluminum		
<b>Fragment</b>	No		Yes
<b>Process Media</b>	Gas, Vapor, Liquid		
<b>Max. Operating Ratio</b>	80%	70%	
<b>Spark</b>	No	Yes	
<b>Option</b>	Pressure Gauge, Burst Sensor, Excess Flow Valve, Alarm System, Long & Short Nipple, Junction Box, Stud Bolt/Nut, PFA/PTFE Coating, Jack Screw, Tee, J-Hook, Plug, Pressure Switch, Reducer		